



Dell 43 Multi-Client Monitor P4317Q

View multi-client content in 43" Ultra HD clarity and enjoy simplified multi-monitor set-ups.

Large, crisp viewing experience

See your work clearly without bezel breaks with the Dell 43 Multi-Client Monitor.

- View super-crisp text and graphs on an expansive 43" screen in Ultra HD 4K or Full HD resolution¹ with no bezel breaks.
- Experience comfortable viewing with a high performance monitor scalar and matte screen.
- Enjoy working with consistent colors across an ultrawide viewing angle.

Multi-client connectivity

Manage your view, productively, with side-by-side or quad-screen viewing.

- Simply connect up to four independent clients to a single monitor to reduce complex multi-monitor mounting and connectivity issues.
- Work productively with side-by-side or quad-screen viewing² thanks to enhanced Dell DisplayManager.³
- Enjoy simplified remote IT department management via RS232 connection on the monitor.



Simplified multi-monitor set-ups

Enjoy easy deployment and maintenance with one large monitor versus four per desk.

- Simplify monitor purchasing, deployment and maintenance with one large versus four independent monitors.
- Easy cable management for a more clutter-free desk with cables from only one versus four monitors.
- Optimize desk and relocation costs with a standardized desk set-up that simplifies IT and facilities management.

Reliability from the #1 monitor brand worldwide*

Comes with Dell's high reliability promise.

- Experience peace of mind from Dell's commitment to quality and customer satisfaction with the Premium Panel⁴ Guarantee.
- Minimize downtime with Dell's 3-year Advanced Exchange Service⁵.
- Enjoy high reliability from the #1 monitor brand worldwide for two consecutive years*.



Thank you for making Dell Monitors
#1 worldwide*

For more information visit www.dell.com/monitors

Easily adjust the panel to your preferred viewing position.



Connectors



- | | |
|---------------------------|-----------------------------------|
| A AC Power | G Audio line-in |
| B RS232 port | H Headphone out |
| C HDMI/MHL | I USB upstream |
| D Mini-DisplayPort | J USB downstream |
| E DisplayPort | K USB downstream (BC1.2)** |
| F VGA | |

What's in the box?

Components

- Monitor panel
- Stand (riser and base)
- VESA cover

Cables

- Power cable (varies by country)
- HDMI, DisplayPort to DisplayPort, mini-DisplayPort to DisplayPort and USB 3.0 upstream cables

Documentation

- Dell Display Manager Software CD
- Drivers and documentation media (CD)
- Quick Setup Guide
- Safety and regulatory information

Dell 43 Multi-Client Monitor | P4317Q

Display

Model number	P4317Q
Viewable image size (diagonal)	107.98 cm (42.51 inches)
Active display area	
Horizontal	941.18 mm (37.05 in)
Vertical	529.42 mm (20.84 in)
Maximum resolution	Ultra HD 4K 3840 x 2160 ⁹ at 60 Hz
Aspect ratio	16:9
Pixel pitch	0.2451 x 0.2451 mm
Brightness (typical)	350 cd/m ²
Color gamut (typical)	72% (CIE 1931), 82% (CIE 1976)
Color depth	1.06 billion colors
Contrast ratio (typical)	1000:1 (typical)
Operating hours (typical)	12/7
Viewing angle (typical) (vertical/horizontal)	178°/178°
Response time (typical)	8ms gray-to-gray
Panel technology, surface	In-plane switching with 2H hardness, anti-glare treatment on the front polarizer
Backlight	LED
Bezel color	Black

Connectivity

Connectors

VGA, HDMI 1.4/MHL combo x2, DisplayPort 1.2⁷, mini-DisplayPort 1.2, USB 3.0⁸ x 4 including 1 charging port + 1 USB 3.0 upstream port; Audio-in, Headphone output, RS232 input port for remote control

Features

Stand	Fixed stand with tilt only (5°±1 (Forward), tilt up: 10°±1 (Backward))
Security	Security lock slot (security lock not included)
VESA mounting support	200 mm x 200 mm
Dell DisplayManager	Picture-by-Picture x 4 and Picture-in-Picture x 2 (with 4 clients)
Speakers	Dual integrated 8W

Power

AC input voltage/frequency/current (typical)	100 VAC to 240 VAC/50 Hz or 60 Hz ± 3 Hz/2 A
Power consumption (normal operation)	70W (typical)
Power consumption (active-off mode)	<0.3 W

Dimensions (with stand)

Height	658.0 mm (25.90 in)
Width	973.1 mm (38.31 in)
Depth	250.0 mm (9.84 in)

Weight

Weight (panel only – no stand)	14.11 kg (31.09 lb)
Weight (with stand)	17.41 kg (38.35 lb)
Shipping weight	24.4 kg (53.78 lb)

Standard service plan

- 3 years Advanced Exchange Service⁵ & Limited Hardware Warranty⁶
- Premium Panel Guarantee⁴

Environmental compliance

China Energy Label, WEEE, ErP(EuP) Standards, Korea E-Standby